



Firma: PROSET VTT doo  
Adresa: Miljakovačka 30v  
Telefon: 063/34-26-29  
Fax: 063/34-26-29  
PIB: 111703442  
E-mail: prodaja@bktuning.rs

## Kamera za rikverc TOYOTA Rav4

Šifra: G6091  
Kategorija proizvoda: TOYOTA  
Proizvođač: OEM

Cena: **4.500,00** rsd.

| Image Sensor          | CMOS PC1030                | CCD OV7959            | CCD PC3030                 | CCD PC 7070                    | CCD PC1089K                    | CCD MT 9V136                 |
|-----------------------|----------------------------|-----------------------|----------------------------|--------------------------------|--------------------------------|------------------------------|
| TV System             | PAL/NTSC                   | PAL/NTSC              | PAL/NTSC                   | PAL/NTSC                       | PAL/NTSC                       | PAL/NTSC                     |
| Effective Pixels      | 648*488Pixels              | 648*488               | 728(H)*488(V)              | 928(H)*500(V)                  | 928(H)*500(V)                  | 720*576/480Pixels            |
| Horizontal resolution | 420TVL                     | 420(TV Line)          | 480TVL                     | 500TVL                         | 500TVL                         | 480TVL                       |
| Sensing area          | 4.08mm*3.12mm              | 4008 um x 3024 um     | 3.584mm*2.688mm            | 3.584mm*2.688mm                | 3.584mm*2.688mm                | 3.584mm*2.688mm              |
| Shutter speed         | 1/60-1/5000                | 1/60-1/5000           | 1/60-1/20000               | 1-1/10000                      | 1-1/10000                      | 1-1/10000                    |
| Minimum Illumination  | 0.1Lux/F=1.2(OLux with ON) | 0.8Lux                | 0.1Lux/F=1.2(Olux with ON) | 0.01Lux/F=1.2(Olux with OR ON) | 0.01Lux/F=1.2(Olux with OR ON) | 0.01Lux/F=1.2(Olux with OR ) |
| Video output          | 1.0vP-Pat 75 ohm           | 1.0vp-p.75 Omega      | 1.0vP-Pat 75 ohm           | 1.0vP-Pat 75 ohm               | 1.0vP-Pat 75 ohm               | 1.0vP-Pat 75 ohm             |
| Power Supply          | DC12V                      | DC12V                 | DC12V                      | DC12V                          | DC12V                          | DC12V                        |
| Operating temperature | -20°C-75°C,RH 95%MAX       | -20°C-75°C,RH 95%MAX  | -20°C-75°C,RH 95% MAX      | -20°C-75°C,RH 95% MAX          | -20°C-75°C,RH 95% MAX          | -20°C-75°C,RH 95% MAX        |
| Storage temperature   | -40°C-85°C,RH 95% MAX      | -40°C-85°C,RH 95% MAX | -40°C-85°C,RH 95% MAX      | -40°C-85°C,RH 95% MAX          | -40°C-85°C,RH 95% MAX          | -40°C-85°C,RH 95% MAX        |
| Lens angle            | 170°                       | 170°                  | 170°                       | 170°                           | 170°                           | 170°                         |
| Waterproof            | IP69K                      | IP68                  | IP69K                      | IP69K                          | IP69K                          | IP69K                        |
| White Balance         | auto                       | auto                  | auto                       | auto                           | auto                           | ato                          |
| AGC                   | Auto                       | Auto                  | Auto                       | Auto                           | Auto                           | Auto                         |
| BLC                   | Auto                       | Auto                  | Auto                       | Auto                           | Auto                           | Auto                         |